

Lean Dolly – Shelf Wagon



Product description

The Lean Dolly – Shelf Wagon has been designed to carry SLC's and component trays widely used within the automotive industry. It is designed to be compatible with both your tugger train and automated systems.

For optimised external transport and warehousing the Lean dolly can be used together with the Lean adaptor pallet.

Benefits

- Improve work flow
- Compatible with the Lean Adaptor Pallet
- Adjustable shelf heights
- Enable reduction of stock level
- Reduce need for floor space
- Improve ergonomics
- Fast and safe truck loading
- Optimize vehicle fill



Lean Dolly – Shelf Wagon

Lean Dolly - Shelf Wagon

External dimensions613 x 404 x 1154 mm

Tare weight (with 4 shelves) 37,5 kg

Wheel size 100 mm wheels

Wheel type 2 fixed & 2 swivel

Wheel materialCPD, rubber or PU

Working capacity:

- CPD – standard and ESD 250 kg
- Rubber – standard and ESD 250 kg
- PU – standard and ESD..... 250 kg

Working load per shelf30 kg

The lowest shelf or base can carry more as it is supported by the Dolly frame.

K.Hartwall wheels are equipped with high quality ball bearings and hub caps for high performance and wheel protection.

Surface treatment: Blue zinc plated acc. to EN-ISO2081


Options

- Total brake on 2 swivel wheels
- RFID & Tracking compatibility


Designed to carry SLC's and trays

- 1 stack of 600 x 400 mm / shelf
- 2 stacks of 300 x 400 mm / shelf
- 4 stacks of 300 x 200 mm / shelf


Standard wheels



Compound wheel



Rubber or rubber ESD wheel



ESD CPD wheel



Polyurethane or polyurethane ESD wheel

